

Basic Series

200
400
800
1200

BITTNER
AUDIO

Intelligent Power

Fixed Installations
Touring
Cinema & Live Theaters
Boardrooms



BASIC - that's meeting the tightest budgets and professional requirements in reliability, flexibility and sound. Alone or in combination with the other products of the Bittner portfolio.

The consequent realisation of the Bittner quality standards indicates once more our understanding of the contracting business. It underlines our philosophy that cost consciousness has nothing to do with giving up standards. Compromise is a word unknown to Bittner Audio!

The incorporation of detent potentiometers, clip limiter, protection circuits for any imaginable situation, as well as a first-class production process using only highest-quality components made the BASIC series the choice of most contractors.


Certainly more than basic!

- High Tech SMT design
- Excellent sound and superior impulse response
- Protection Circuits: DC, LF, HF, Thermal, Short Circuit, Current Limiter, 3 ms Muting Delay
- XLR Inputs
- Speakon and Binding Posts
- Clip Limiter
- Toroidal transformers
- LED Indicators for SIGNAL, CLIP, PROTECT, POWER
- Temperature controlled, variable speed, low noise fans
- Detent potentiometers
- Stereo/Bridged/Parallel Mode
- Ground Lift
- Robust Steel Chassis
- 3 Year Warranty

BASIC Series

BITTNER
AUDIO

Intelligent Power



Connectors and Controls of the rear panel

Audio InputsXLR connectors

Loudspeaker Outputs.....SPEAKON and 4-pin screw terminals

Groundlift2 position switch: Chassis Earth and Audio Ground are either connected or seperated

Amp Mode3 position switch: STEREO, PARALLEL or BRIDGED

PowerFixed 230 V cord, fuse

DECLARATION OF CONFORMITY

We declare that this product is in accordance with EMC regulation 89/336/EEC and meets the requirements of the product norm EN-55013 (emission), and EN-55020 (immission).

All Specifications Subject to Change Without Notice

All Specs under www.bittner-audio.com